

Accesorios para conectividad de tubos. Acero Galvanizado
Accessoires de connectivité. Acier galvanisé.
Accessories for duct connection. Galvanised steel.



Tubo de PVC · Gaine souple de PVC · PVC duct. 60 µm

Ø mm	Ø cm	2,5 m	5 m
Ø - 80	Ø - 83	081283	081290
Ø - 100	Ø - 103	081306	081313
Ø - 110	Ø - 113	081320	081337
Ø - 125	Ø - 128	081344	081351
Ø - 150	Ø - 153	081368	081375



Velocidad del aire - Vitesse de l'air - Air speed : MAX 20 m/s
Temperatura - Température - Temperature : MIN/MAX -20/+70°C
Presión - Pression - Pressure : Max. 1500 Pa
Difícil ignición - Difficile à enflammer - Difficult to ignite

Tubo flexible en alu. · Gaine souple d'alu · Flexible alu. duct 74 µm

Ø mm	Ø cm	2,5 m	10 m
Ø - 80	Ø - 84	081382	081399
Ø - 100	Ø - 104	081405	081412
Ø - 110	Ø - 114	081429	081436
Ø - 125	Ø - 129	081443	081450
Ø - 150	Ø - 154	081467	081474



Velocidad del aire - Vitesse de l'air - Air speed : MAX 30 m/s
Temperatura - Température - Temperature : MIN/MAX -30/+150°C
Presión - Pression - Pressure : Max. 3000 Pa
Difícil ignición - Difficile à enflammer - Difficult to ignite



Tubo flexible semirrígido en aluminio 70 µm
Gaine de 70 µm d'aluminium semi-rigide
Flexible semi-rigid aluminium duct 70 µm

Ø mm	Ø cm	1,5 m	3 m
Ø - 80	Ø - 85	081481	081498
Ø - 100	Ø - 105	081504	081511
Ø - 110	Ø - 115	081528	081535
Ø - 125	Ø - 130	081542	081559
Ø - 150	Ø - 155	081566	081573



Velocidad del aire - Vitesse de l'air - Air speed : MAX 30 m/s
Temperatura - Température - Temperature : MIN/MAX -30/+250°C
Presión - Pression - Pressure : Max. 3000 Pa
No inflamable - Pas inflammable - Not flammable

